

# Dled+plus

Downlight con led de alto rendimiento, CRI 80. IP-44  
 Ceiling lighting with led high efficiency, CRI 80. IP-44

ACABADO / FINISHES:

Blanco / White

Cristal Transparente / Clear Glass


Cristal Difuso / Frost Glass

MEDIDAS / MEASUREMENTS:


ø 240x67mm / ø 195x70mm

MEDIDA INSTALACION / INSTALL MEASUREMENTS:

ø 210mm / ø 170mm



Ø 240mm	REF.	N.LEDS	COLOR	LIGHT FLOW	ALIM./POWER	W	ANGULO/BEAM ANGLE	CRISTAL/GLASS
	DLPL-101-F15	1	5.000°K	3.265 Lm	220-240Vac	24W	70°	TRANSP./CLEAR
	DLPL-101-F14	1	4.000°K	3.240 Lm	220-240Vac	24W	70°	TRANSP./CLEAR
	DLPL-101-F13	1	3.000°K	3.130 Lm	220-240Vac	24W	70°	TRANSP./CLEAR
	DLPL-101-D15	1	5.000°K	3.265 Lm	220-240Vac	24W	70°	TRANSP./CLEAR
	DLPL-101-D14	1	4.000°K	3.240 Lm	220-240Vac	24W	70°	TRANSP./CLEAR
	DLPL-101-D13	1	3.000°K	3.130 Lm	220-240Vac	24W	70°	TRANSP./CLEAR
	DLPL-102-F15	1	5.000°K	2.740 Lm	220-240Vac	24W	90°	DIFUSO/FROST
	DLPL-102-F14	1	4.000°K	2.720 Lm	220-240Vac	24W	90°	DIFUSO/FROST
	DLPL-102-F13	1	3.000°K	2.630 Lm	220-240Vac	24W	90°	DIFUSO/FROST
	DLPL-102-D15	1	5.000°K	2.740 Lm	220-240Vac	24W	90°	DIFUSO/FROST
	DLPL-102-D14	1	4.000°K	2.720 Lm	220-240Vac	24W	90°	DIFUSO/FROST
	DLPL-102-D13	1	3.000°K	2.630 Lm	220-240Vac	24W	90°	DIFUSO/FROST
	DLPL-103-F15	1	5.000°K	2.398 Lm	220-240Vac	17W	70°	TRANSP./CLEAR
	DLPL-103-F14	1	4.000°K	2.380 Lm	220-240Vac	17W	70°	TRANSP./CLEAR
	DLPL-103-F13	1	3.000°K	2.300 Lm	220-240Vac	17W	70°	TRANSP./CLEAR
	DLPL-103-D15	1	5.000°K	2.398 Lm	220-240Vac	17W	70°	TRANSP./CLEAR
	DLPL-103-D14	1	4.000°K	2.380 Lm	220-240Vac	17W	70°	TRANSP./CLEAR
	DLPL-103-D13	1	3.000°K	2.300 Lm	220-240Vac	17W	70°	TRANSP./CLEAR
	DLPL-104-F15	1	5.000°K	2.013 Lm	220-240Vac	17W	90°	DIFUSO/FROST
	DLPL-104-F14	1	4.000°K	1.999 Lm	220-240Vac	17W	90°	DIFUSO/FROST
	DLPL-104-F13	1	3.000°K	1.931 Lm	220-240Vac	17W	90°	DIFUSO/FROST
	DLPL-104-D15	1	5.000°K	2.013 Lm	220-240Vac	17W	90°	DIFUSO/FROST
	DLPL-104-D14	1	4.000°K	1.999 Lm	220-240Vac	17W	90°	DIFUSO/FROST
	DLPL-104-D13	1	3.000°K	1.931 Lm	220-240Vac	17W	90°	DIFUSO/FROST
<b>Ø 195mm</b>	DLPL-201-F15	1	5.000°K	2.265 Lm	220-240Vac	17W	50°	TRANSP./CLEAR
	DLPL-201-F14	1	4.000°K	2.240 Lm	220-240Vac	17W	50°	TRANSP./CLEAR
	DLPL-201-F13	1	3.000°K	2.170 Lm	220-240Vac	17W	50°	TRANSP./CLEAR
	DLPL-201-D15	1	5.000°K	2.265 Lm	220-240Vac	17W	50°	TRANSP./CLEAR
	DLPL-201-D14	1	4.000°K	2.240 Lm	220-240Vac	17W	50°	TRANSP./CLEAR
	DLPL-201-D13	1	3.000°K	2.170 Lm	220-240Vac	17W	50°	TRANSP./CLEAR
	DLPL-202-F15	1	5.000°K	1.900 Lm	220-240Vac	17W	75°	DIFUSO/FROST
	DLPL-202-F14	1	4.000°K	1.880 Lm	220-240Vac	17W	75°	DIFUSO/FROST
	DLPL-202-F13	1	3.000°K	1.820 Lm	220-240Vac	17W	75°	DIFUSO/FROST
	DLPL-202-D15	1	5.000°K	1.900 Lm	220-240Vac	17W	75°	DIFUSO/FROST
	DLPL-202-D14	1	4.000°K	1.880 Lm	220-240Vac	17W	75°	DIFUSO/FROST
	DLPL-202-D13	1	3.000°K	1.820 Lm	220-240Vac	17W	75°	DIFUSO/FROST



**OBSERVACIONES / NOTES**

Fuente de alimentación incluida.  
 Power supply included.